



VERSADJUST
Adjustable Deck Supports

STRENGTH AND SUPERIOR FUNCTIONALITY

VERSADJUST ADJUSTABLE DECK SUPPORT

May 2013

- Loaded with features for superior functionality
- Integral base leveling to correct for sloping surfaces
- Add quick-clip couplers to reach heights fast - up to 36 inches
- Pedestal bracing system available
- Fast and easy installation - promotes labor savings
- Screw-to-adjust pedestals assures perfectly level decks
- Impervious to water and long lasting
- Unique design: Patents Pending
- **Made in the U.S.A.**



US Patent and Patents Pending. Copyright 5-1-2013 United Construction Products, Inc. All Rights Reserved.

BISON INNOVATIVE PRODUCTS | 2395 W. 4TH AVENUE, DENVER, CO 80223 USA | 800-333-4234 | INFO@BISONIP.COM | BISONIP.COM

SPECIFICATIONS

- Supports heaviest load: 1,250 lbs per pedestal (FS:3)
- Integrated Base Levelers accommodate 0 to 1/2 inch per foot slope*
- Versadjust adjustable system height range is 2 1/4 inches to 36 inches
- Accessories for heights from 1/8 inch to 2 1/4 inches
- Contains 20% Post-Industrial Recycled Material
- Impervious to water, mold and freeze/thaw
- Usually ships in 1 - 2 business days
- **Made in the U.S.A.**

	Model No.	Description	Height Range	Max Height	
		V1-18 V1-316 Adjustable Pedestal* <small>(Select 1/8" or 3/16" Tab Size)</small>	2 1/4" - 2 3/4"	2 3/4"	
		V2-18 V2-316 Adjustable Pedestal* <small>(Select 1/8" or 3/16" Tab Size)</small>	2 3/4" - 3 3/4"	3 3/4"	
		V3-18 V3-316 Adjustable Pedestal* <small>(Select 1/8" or 3/16" Tab Size)</small>	3 3/4" - 5 3/4"	5 3/4"	
		V4-18 V4-316 Adjustable Pedestal* <small>(Select 1/8" or 3/16" Tab Size)</small>	5 3/4" - 9"	9"	
Tabs		VC2 Quick Clip Coupler	Insert VC2 into V4 Base or other VC2s Adds 4" each	Utilize up to 4 VC2's to reach 24" Must use Bison Brace for 24"-36" in height	
		VT18 VT316 Tab	1/8" wide 3/16" wide		
		VT18 VT316 Use for Ultra Low Support <small>(Select 1/8" or 3/16" Tab Size)</small>	1/8"	1/8"	
		HD25-18 HD25-316 HD50-18 HD50-316 HD75-18 HD75-316 Fixed Height Stackable Pedestals <small>(Select 1/8" or 3/16" Tab Size)</small>	1/4" 1/2" 3/4"	Stack up to 4	
		LO-18 LO-316 Low Height Adjustable Pedestal <small>(Select 1/8" or 3/16" Tab Size)</small>	1 1/4" - 2"	2"	
		B11 Flexible Shim	1/16"	1/16"	
		PS1 Rigid Shim	1/8"	1/8"	
	Accessories		LD4 Base Leveler	1/4"-1" per foot slope Add up to 2 more with Versadjust	3/8" center thickness
			FS1 Wood Tile Fastening Kit		Secure Bison Wood Tiles to pedestal system.
			BB Wedge Bison Wedge Spacers		adds 3/16" in width nominal
		JT Joist Top <small>(Works with 2"x and 4"x Lumber)</small>		adds 3/16" in height	
		FIB Floating Insulation Base		12" x 12" x 11/16" For use over roofing systems with less than 40 psi bearing capacity	
		FFB Floating Foundation Base		12" x 12" x 1/4" For use on grade (soil) under each pedestal.	

US Patents Pending. Copyright 5-1-2013 United Construction Products, Inc. All Rights Reserved.

